

▶ Power wheelchairs | Indoor / outdoor

Skippi / Skippi^{Plus}

The power wheelchair for kids



Crash test
in accordance with
ISO 7176-19 in
accordance with
ANSI/RESNA

▶ Power wheelchairs | Indoor / outdoor

Standard model

- Standard seat with back bag
- Seat cushions
- Telescoping side panels
- Drive wheels with aluminium rim, black
- Wheel cover for drive wheels
- 8" PU caster wheel
- Individual telescoping footrests
- 28 Ah (C5) AGM batteries
- Battery charger
- **Skippi: enAble40 control unit** with the ability to control 2 electric options (choice of: electric back angle adjustment, electric seat tilt and electric seat height adjustment)
- **SkippiPlus: enAble50 control unit** with the ability to control 3 electric options (choice same as Skippi as well as special and environmental controls)
- Frame colours: depending on frame colour combination, upholstery in red / black, blue / black

Options / equipping possibilities

- Push handles, height-adjustable
- Attendant control
- Electric back adjustment
- Electric seat tilt
- Electric seat height adjustment (SkippiPlus)
- Bumper bar, detachable
- Footrest with single-panel aluminium footplate
- Self-contacting LED front lighting and LED rear lighting in accordance with German Motor Vehicle Safety Standards (StVZO)
- Manual horn
- Vehicle transportation kit

Custom fabrications

- Seating shell adapter
- Seat height 480 mm

See order form for further options/custom fabrications also available upon request.



- Quick to disassemble, therefore easy to stow and transport



- Telescoping side panels

Options



- Push handles, height adjustable / detachable




- Attendant control




- Electric back adjustment



- Electric seat tilt



- Bumper bar, removable (only up to LL 320 mm)



- LED lighting according to German Motor Vehicle Safety Standards (StVZO)



- Manual horn



- Vehicle transportation kit (prerequisite AMF anchor point system)

Technical data

Speed	6 km/h
Battery capacity	28 Ah (C5) AGM batteries
Range under test conditions approx.	25 km
Control unit	Skippi (enAble40) Skippi ^{Plus} (enAble50)
Max. user weight	50 kg
Max. obstacle negotiation height (optional)	50 mm
Climbing ability	12 % (7°)
Length including footplates	850 mm
Width	570 mm
Turning radius	680
Seat height (without cushion), at 3° seat tilt	430 mm

Seat width	300–380 mm
Seat depth	280–380 mm
Back angle	-9° to +30°
Seat tilt	25° mechanical, 20° electric
Seat inclination	0°/3°/6°
Back height	340/460 mm
Armrest height	170–230 mm
Lower leg length	150–380 mm
Weight when empty	62 kg
Max. charging time	12 h
Skippi ^{Plus} with electric seat height adjustment	200 mm