

FUNCTIONS



Backrest adjustment : 0 - 70°



Trendelenburg position : 0 - 12°



Upper platform is able to be transferred from one trolley to other trolley.

GENERAL SPECIFICATIONS

- Antibacterial and cleanable artificial leather covered, high density foam mattress.
- Owing to resistant and useful rail system, upper platform is able to be transferred from one trolley to other trolley.
- Backrest position is adjusted by gas spring between 0-65 degrees by pulling black control handle.
- Trendelenburg position is adjusted by gas spring between 0-12 degrees by pulling black control handle.
- Ergonomic, durable and easily cleanable metal rails system with maximum safety.
- There are four bumpers on corners of bed for protection against to surrounding
- There is an oxygen tube holder.
- Epoxy painted steel construction is, resistant to corrosion.
- Moves easily by 150 mm diameter castors.
- Optional vinlex color choice. ^(RvX)

TECHNICAL SPECIFICATIONS


- Width : 70,5 cm
- Length (one trolley) : 213 cm
- Length (two trolley) : 404,5 cm
- Weight : approx 122 kg
- Volume : 2,60 m³

OPTIONS

GROUP 1 / CASTOR OPTIONS



T11




T12

GROUP 2 / IV STAND OPTIONS



W0



W8

DESCRIPTION OF OPTION CODES

- T11 CASTOR TWO WITH BRAKE (150 MM)
- T12 CASTOR CENTRAL & DIRECTIONAL LOCK (150 MM)
- W0 WITHOUT OTHER ACCESSORIES
- W8 IV STAND : ONE HEIGHT ADJUSTMENT SYSTEM

■ Must select only one of them.





* RV : Vinlex color options page 81.