

THERMOTHERAPY



PARAFFIN BATH (30L.) - G.18907

Paraffin heater using the "bain-marie" method.
 Mobile (four twin casters with brakes).
 Both tank interior and basin exterior made from AISI 304 stainless steel.
 Insulating wooden rim.
 Safety mechanism to prevent boiling.
 Thermostat: range from 0 to 90°.
 Water level gauge for the internal basin visible from the side.
 Front panel equipped with on/off switch, pilot switch and thermostat.
 Maximum filling capacity 30L. Recommended: 22 liters.
 Convenient paraffin and water emptying system via drain outlets on the underside of the basin.
 Voltage: 220-240V / 50-60Hz. On request 110-127V / 50-60Hz.
 Class II Product.
EC Certificate Ila n° ES13/15115.



OPTIONAL:

REMOVABLE TROLLEY FOR PARAFFIN BATH - G.18907/1

Fitted with two trays, two handles and four wheels. Stainless steel construction.

PARAFFIN FILTER - G.18907/2

Filter impurities from the paraffin, keeping it clean for longer.

Stainless steel construction, fitted with handles.

1 kg. PARAFFIN WAX BAR - G.18910



PARAFFIN BATH (2L.) - G. 18908

Fitted with on/off switch and power on indicator light.
 Capacity: 2 litres.
 Includes: Paraffin, 100 plastic bags and 2 mitts.
 Voltage: 220-240V / 50-60Hz. For 110-127V / 50-60 Hz transformer is required.



INFRA-RED LAMP - G.18900

INFRA-RED LAMP WITH TIMER - G.18900-A

Multi-directional focus. Anodized aluminium reflective screen.
 Adjustable height. Moveable base fitted with 5 wheels.
 Equipped with timer from 0 to 60 minutes, programmable with automatic cut-off. (Model G.18900-A).
 Voltage: 220-240V / 50-60Hz. On request 110-127V / 60Hz
 Class II Product.
EC Certificate Ila n° ES13/15115.

TABLE-TOP INFRA-RED RAY LAMP - G.18901

Voltage: 220-240V / 50-60Hz. For 110-127V / 50-60 Hz transformer is required.