

ORDERING INFORMATION

Part Number Description

M-2 Mobile Hydrocollator

| | |
|--------|--|
| 2402 | M2 Mobile - Includes 12 Standard (1006) HotPacs |
| 2402-2 | M2 Mobile - Includes 3 Standard (1006), 3 Oversize (1004), and 3 Cervical (1002) HotPacs |
| 2402-3 | M2 Mobile - Includes 4 Standard (1006), 2 Oversize (1004), and 4 Cervical (1002) HotPacs |
| 2402-4 | M2 Mobile - Includes 4 Standard (1006), and 4 Oversize (1004) |

M-4 Mobile Hydrocollator

| | |
|--------|--|
| 2502 | M4 Mobile - Includes 24 Standard (1006) HotPacs |
| 2502-2 | M4 Mobile - Includes 8 Oversize (1004), and 8 Cervical (1002) HotPacs |
| 2502-3 | M4 Mobile - Includes 6 Standard (1006), 6 Oversize (1004), and 6 Cervical (1002) HotPacs |

SS-2 Mobile Hydrocollator

| | |
|--------|---|
| 2302 | SS2 Mobile - Includes 8 Standard (1006) HotPacs |
| 2302-2 | SS2 Mobile - Includes 4 Standard (1006), and 4 Cervical (1002), HotPacs |
| 2302-3 | SS2 Mobile - Includes 2 Standard (1006), 2 Oversize (1004), and 2 Cervical (1002) HotPacs |

TECHNICAL SPECIFICATIONS

M-2 Mobile Hydrocollator

| | |
|---------------------------|---|
| Mains Power: | 110-120 V, 50/60 Hz |
| Power Consumption: | 1000 W |
| Weight: | 48 lb (22 kg) /Shipping - 93 lb (42 kg) |
| Dimensions ^o : | 27" x 16" x 33" (69 x 41 x 84 cm) |
| Electrical Safety Class: | Class 1, Type B |
| Safety Tests: | Conforms to UL 60601-1, certified to Can/CSA C222 No. 601.1 |

M-4 Mobile Hydrocollator

| | |
|---------------------------|---|
| Mains Power: | 110-120 V, 50/60 Hz |
| Power Consumption: | 1500 W |
| Weight: | 132 lb (60 kg) /Shipping - 160 lb (72 kg) |
| Dimensions ^o : | 35" x 20" x 33" (89 x 51 x 84 cm) |
| Electrical Safety Class: | Class 1, Type B |
| Safety Tests: | Conforms to UL 60601-1, certified to Can/CSA C222 No. 601.1 |

SS-2 Mobile Hydrocollator

| | |
|---------------------------|---|
| Mains Power: | 110-120 V, 50/60 Hz |
| Power Consumption: | 1000 W |
| Weight: | 66 lb (30 kg) /Shipping - 80 lb (36 kg) |
| Dimensions ^o : | 21" x 16" x 33" (53 x 41 x 84 cm) |
| Electrical Safety Class: | Class 1, Type B |
| Safety Tests: | Conforms to UL 60601-1, certified to Can/CSA C222 No. 601.1 |

^o Dimensions are listed as L x W x H

HYDROCOLLATOR® MOBILE HEATING UNITS



Our benchmark product is the standard all others can only hope to match. Durable and easy to maintain, these high-quality stainless steel units give you a constant supply of temperature-consistent HotPacs.



FEATURES

Hydrocollator Mobile Heating Units

- High-quality stainless steel
- Thermostatically controlled temperature
- 3" (8 cm) swivel-type rubber casters for silent, friction-free movement
- Easy maintenance. Simple to fill and drain. No plumbing required
- One-year warranty

* Approximate with HotPacs

| | M-2 | M-4 | SS-2 | E-2 | E-1/E-1 MHT |
|--|---------------------------|---------------------------|---------------------------|---------------------------|---------------------------|
| Tank Capacity | 14 gal (52 L) | 27 gal (102 L) | 10 gal (37 L) | 8 gal (37 L) | 3 gal (37 L) |
| Temperature Range | 160° - 165°F (71° - 74°C) | 160° - 165°F (71° - 74°C) | 160° - 165°F (71° - 74°C) | 160° - 165°F (71° - 74°C) | 160° - 165°F (71° - 74°C) |
| Thermal Cut-Out Temp. | 180° - 185°F (82° - 85°C) | 180° - 185°F (82° - 85°C) | 180° - 185°F (82° - 85°C) | 180° - 185°F (82° - 85°C) | 180° - 185°F (82° - 85°C) |
| Temperature Accuracy | +/- 10% | +/- 10% | +/- 10% | +/- 10% | +/- 10% |
| Heat up Time to 160° F (to 70°C) | 6 Hours | 8 Hours | 4 Hours | 4 Hours | 2 Hours |
| Cool Down Time from 160° F (from 70°C) | 3 Hours | 4 Hours | 4 Hours | 2 Hours | 1 Hour |
| Fiberglass Insulation | Yes | Yes | Yes | No | No |